



200W Bicolor LED Fresnel Spot Light

VG-PB200W-C

Technical Specification Sheet



VanGaa: Focus on
Studio Lighting Fixtures



www.VanGaa.com

Building B, Langling Industry Park, DS Road, Huadu District, Guangzhou
Tel: 86 20 86432439 Fax: 86 20 36880919
Homepage: www.vangaa.com, Email: info@vangaa.com



VG-PB200W-C 200W Bicolor LED Fresnel Spot Light


This television projector light equips high power 200W LED lamps as the light source, it's energy saving. And it uses high efficiency optical lens, light soft. It's a best choice for film and television performances, studio and other places.



Features

- Controlled by DMX-512, very convenient;
- Using two color COB led, from 3200K-5600K;
- Can realize 0-100% dimmer, 16 bit;
- Adopts outside frame design, beautiful;
- Installation very convenient, safe and reliable;
- Brighter than 2000W Tungsten Halogen fresnel spot light;
- 3200K light put can reach 3780lux @ 2 meters;
- 3200K CCT, 4000K CCT, 5600K CCT and 6500K CCT are included;
- Auto range voltage AC90-240V, 50/60Hz;
- Up to 90% energy savings;
- Precise brightness control w/variable dimming curve;
- Single light source eliminates multiple shadows;
- Flicker-free up to 12,000 fps;
- No heat generation- cooling by fan and radiators;
- 15-60degree beam angle, manual or DMX zoom;
- Built-in digital user interface module control;
- International standard 3/5pins XLR DMX in/DMX out connon;
- Neutrik Powercon connection;
- Programmable multiple lighting with strobe effects;
- 1+4 years warranty on fixture;
- Operating temperature at -20c tp +50c;
- Certified CCC, CE & RoHs compliant.





Technical Specification

Light Sources

- LED: 1pc 200W Bi color COB LED Lamps
- Lifespan: 500,000h
- Color: from CW to WW, 2700K-6000K adjustable

Optics

- Beam angle: 15-60degree
- Dimmer: 0~100%
- CRI: Ra>92

Light Output

- Luminous flux: 9775.3lm
- Illuminance: 2700 Lux (6m 15°)
- Optimal projection distance: 17-40m

Control

- Control mode: DMX-512; Auto run
- DMX channel: 3CH, 4CH
- Display of control panel: LCD display +

Power Supply

- Related voltage: AC100V-240V, 50/60Hz
- Related power: 300W

Construction

- Body dimension: D455*W265*H292mm
- Net weight: 8.5kg
- Shell color: black
- Housing material: aluminum alloy

Working Environment

- Working temperature: -25-40
- Cooling: copper tube convactor + mute fan
- Protection rating: IP20



Spare Parts

- Cable: 1set DMX in and DMX out signal cable, and 1set Power in and Power out power cable with plug [standard configuration]
- Light visor: 1pc light visor [optional configuration]

Package

- Carton board: 510*320*370mm(1pc/carton)
- N.W/G.W/V.W: 8.5kg/10kg/13kg







Dimension



8.5kg(18.74lb)



DMX Channel Chart

5CH	1	2	3	4	5
%	General Dimmer	Fixed Color Temp.	WW Dimmer	CW Dimmer	Strobe
					

Lux Chart

